

Product Specification of:

NO₂ - Industrial Sensor / Type I-50



:: KEY FEATURE ::

Amperometric gas sensor shows low interferences to other gases and has a fast response time.

All characteristics are based on conditions at 25°C, 50% RH and 1013 hPa.

Operating Principle:	3-electrode potentiostatic cell w/o potentiostat	
Electrical Connector:	3-pin Molex®	
Sensor Lifetime:	~ 2 years	
Gas Connector:	M16 x 1 thread	
Measurement Range:	0 to 500 ppm	
Maximum Overload:	up to 2,000 ppm	
Sensitivity:	- 150 to - 250 nA/ppm	
Response Time t₉₀:	< 15 s	
Warm-up Time:	< 1 h, when connected to bias	
Bias Voltage:	0 mV	
Drift:	< 10 % signal/year	
Zero Offset Current:	< ± 1 ppm	
Operating Temperature:	0 to 50 °C	
Pressure Range:	750 to 1250 hPa	
Humidity Range:	30 to 98 % RH	
Interferences:	CO ₂ : none	SO ₂ : < 5 nA/ppm
	CO: < 1 nA/ppm	H ₂ S: < 30 nA/ppm
	H ₂ : < 1 nA/ppm	NO: < 2 nA/ppm
	O ₂ : none	
Weight:	approximately 13 g	
Material in Contact with Media:	PP, PPS, PTFE, stainless steel	



:: STORAGE CONDITIONS ::

Temperature Range:	recommended: 5 to 30 °C
	maximum: -20 to 50 °C
Ambient Pressure:	600 to 1250 hPa
Humidity:	10 to 98 % RH
Shelf Life:	< 3 months recommended

:: RELATED PRODUCTS ::

Product	Part-No.	Housing Colour
NO ₂ - Sensor I-50	48 00 09	grey

This data sheet is subject to change without prior notice. [I-50-Rev_022012.doc]

page 1 of 1